

Drop-Ceiling Flush-Mount Speakers

CR8 SERIES – ROUND TEXTURED 11" WHITE PLASTIC CEILING BAFFLE

- ST4-CR8** 5 oz dual cone speaker with 4W, 25/70V xfrmr.
- SDT4-CR8** 10 oz dual cone speaker with 4W, 25/70V xfrmr.
- ST4P-CR8** 5 oz dual cone speaker with 4W, 25/70V xfrmr & v/c.
- SDT4P-CR8** 10 oz dual cone speaker with 4W, 25/70V xfrmr & v/c.
- ST5-CR8** 5 oz dual cone speaker with 5W, 70V xfrmr.
- ST5P-CR8** 5 oz dual cone speaker with 5W, 70V xfrmr & v/c.



CR8W

RE8 SERIES - ROUND TEXTURED 11" WHITE STEEL CEILING BAFFLE


- ST4-RE8** 5 oz dual cone speaker with 4W, 25/70V xfrmr.
- SDT4-RE8** 10 oz dual cone speaker with 4W, 25/70V xfrmr.
- ST4P-RE8** 5 oz dual cone speaker with 4W, 25/70V xfrmr & v/c.
- SDT4P-RE8** 10 oz dual cone speaker with 4W, 25/70V xfrmr & v/c.
- ST5-RE8** 5 oz dual cone speaker with 5W, 70V xfrmr.
- SDT12-RE8** 10 oz dual cone speaker with 12W, 70V xfrmr.
- SCT12-RE8** 10 oz coaxial speaker with 12W, 70V xfrmr.



RE8W

BS8 SERIES - ROUND TEXTURED 12 1/2" WHITE STEEL CEILING BAFFLE

- ST4-BS8** 5 oz dual cone speaker with 4W, 25/70V xfrmr.
- SDT4-BS8** 10 oz dual cone speaker with 4W, 25/70V xfrmr.
- ST4P-BS8** 5 oz dual cone speaker with 4W, 25/70V xfrmr & v/c.
- SDT4P-BS8** 10 oz dual cone speaker with 4W, 25/70V xfrmr & v/c.



BS8W

CR8 Series	ST4-CR8	SDT4-CR8	ST5-CR8	ST4P-CR8	SDT4P-CR8	ST5P-CR8
Primary Taps, Watts	4, 2, 1, 0.5	4, 2, 1, 0.5	5, 2.5, 1, 0.5, 0.25	4, 2, 1, 0.5	4, 2, 1, 0.5	5, 2.5, 1, 0.5, 0.25
Magnet Weight	5 oz	10 oz	5 oz	5 oz	10 oz	5 oz
Freq Resp-Speaker	40Hz-18KHz	30Hz-18KHz	40Hz-18KHz	40Hz-18KHz	30Hz-18KHz	40Hz-18KHz
Freq Resp-Transformer	80Hz-16KHz	80Hz-16KHz	80Hz-16KHz	80Hz-16KHz	80Hz-16KHz	80Hz-16KHz
Sensitivity	96 db	100 db	96 db	96 db	100 db	96 db
Primary Volts	25, 70	25, 70	70	25, 70	25, 70	70
Volume Control	No	No	No	Yes	Yes	Yes

RE8 Series	ST4-RE8	SDT4-RE8	ST5-RE8	SDT12-RE8	SCT12-RE8	ST4P-RE8	SDT4P-RE8
Primary Taps, Watts	4, 2, 1, 0.5	4, 2, 1, 0.5	5, 2.5, 1, 0.5, 0.25	12, 6, 3, 1	12, 6, 3, 1	4, 2, 1, 0.5	4, 2, 1, 0.5
Magnet Weight	5 oz	10 oz	5 oz	10 oz	10 oz	5 oz	10 oz
Freq Resp-Speaker	40Hz-18KHz	30Hz-18KHz	40Hz-18KHz	30Hz-18KHz	30Hz-18KHz	40Hz-18KHz	30Hz-18KHz
Freq Resp-Transformer	80Hz-20KHz	80Hz-20KHz	80Hz-20KHz	80Hz-20KHz	80Hz-20KHz	80Hz-20KHz	80Hz-20KHz
Sensitivity SPL/1W/1M	96 db	100 db	96 db	100 db	97 db	96 db	100 db
Primary Volts	25, 70	25, 70	70	25, 70	25, 70	25, 70	25, 70
Volume Control	No	No	No	No	No	Yes	Yes

BS8 Series	ST4-BS8	ST4P-BS8	SDT4-BS8	SDT4P-BS8	EJ8 Series	ST5-EJB	ST5P-EJB
Primary Taps, Watts	4, 2, 1, 0.5	4, 2, 1, 0.5	4, 2, 1, 0.5	4, 2, 1, 0.5	Primary Taps, Watts	5, 2.5, 1, 0.5, 0.25	5, 2.5, 1, 0.5, 0.25
Magnet Weight	5 oz	5 oz	10 oz	10 oz	Magnet Weight	5 oz	5 oz
Freq Resp-Speaker	40Hz-18KHz	40Hz-18KHz	30Hz-18KHz	30Hz-18KHz	Freq Resp-Speaker	40Hz-18KHz	40Hz-18KHz
Freq Resp-Transformer	80Hz-20KHz	80Hz-20KHz	80Hz-20KHz	80Hz-20KHz	Freq Resp-Transformer	80Hz-20KHz	80Hz-20KHz
Sensitivity SPL/1W/1M	96 db	96 db	100 db	100 db	Sensitivity SPL/1W/1M	96 db	96 db
Primary Volts	25, 70	25, 70	25, 70	25, 70	Primary Volts	70	70
Volume Control	No	Yes	No	Yes	Volume Control	No	Yes